

698-3800MHz Power Splitter 2/3/4 way 4.3-10 Female

- Wide frequency range 380 to 3800 MHZ for 2G/3G/4G applications
- Low passive intermodulation 160dBc
- Low VSWR & insertion loss
- Indoor & outdoor use; IP65
- Connector Type N, 7/16 DIN or 4.3/10 Available



Specifications :

Part No.	9508320050	9508330050	9508340050
Electrical			
Frequency range (MHz)	698-3800		
VSWR	≤1.25		
Insertion Loss(dB)	2way ≅ 3.0±0.4	3way ≅ 4.8±0.5	4way ≅ 6.0±0.6
Intermodulation (dBc)	≤-160dBc (with 2×43dBm)		
Impedance (Ω)	50 Ω		
Input power (W)	300		
Environmental			
Operation temperature	-40 °C to +65 °C		
Storage temperature	-55 °C to +85 °C		
Relative humidity	5% - 95%		
Application	Indoor or outdoor (IP65)		
Mechanical			
Connector	4.3-10-Female/N Female/DIN Female		
Color	Black or customized based on requirements		
Weight(kg)	0.25	0.35	0.45
Dimension(mm)	2way :157*25*25	3way :188*25*25	4way :188*25*25

Outline Drawing :

