

## 694-3800MHz Strip line Power Splitter 2way 4.3-10 Female

- Wide frequency range 694 to 3800 MHz for 2G/3G/4G/5G applications
- Low passive intermodulation 150dBc
- Low VSWR & insertion loss
- Indoor & outdoor use; IP65
- Connector Type N/ 4.3/10 /7-16 DIN Available

### Specifications :

Part No.	9528320250
<b>Electrical</b>	
Frequency range (MHz)	694-3800
VSWR: 694 – 2700 MHz	≤ 1.3 (Port 1)
2700 – 3800 MHz	≤ 1.4 (Port 1)
Insertion Loss(dB):	
694 – 2700 MHz	3.1 dB ± 0.2 dB
2700 – 3800 MHz	3.1 dB ± 0.3 dB
Intermodulation (dBc)	≤-150dBc (with 2×43dBm)
Impedance (Ω)	50 Ω
Input power (W)	300
<b>Environmental</b>	
Temperature range	-25°C ~ +55°C
Phase difference	≤ 20°
Application	Indoor or outdoor (IP65)
<b>Mechanical</b>	
Connector	4.3-10-Female
Color	Grey
Weight(kg)	0.40
Dimension(mm)	78.7mm×73.5mm×23.5 mm

### Product Image:



Outline drawing : 2 way

